

# SCHULTE®

*Fighter Series*

## FX210 ROTARY CUTTER



- Trailing unit shown above with **non-cv** equal angle hitch -



- Semi-mount swing unit shown above -



- Semi-mount unit shown above -  
- Non-Swing -

## Trailing, Semi-Mount & Semi-Mount Swing Unmatched Versatility

- 1** New domed deck design.
- 2** New equal angle hitch non-cv drive. (Trailing unit only)
- 3** Semi mount swing unit has the capability of swinging 16" to left or right of center. This 32" of lateral movement offers the industries' widest swing.
- 4** Deck protection rings.
- 5** New sloped back design improves spread of cut material.
- 6** Trailing unit offers a floating hitch for better ground following.
- 7** Adjustable wheel standards.

G O N U M B E R O N E . . . G O S C H U L T E !

# Trailing, Semi-Mount & Semi-Mount Swing Unmatched Versatility



- Semi-mount unit showing left and right swing -

- Down Boxes are rated at 190 hp and the T-Box is rated at 205 hp.
- Down Boxes have 1.75" 20 spline input shafts and 2.375" down shafts.
- T-Box has 1.75" 20 spline input and output shafts.
- Drive line is low maintenance featuring high strength star profile tubing with Rilsan (low friction) coating. Cross kits require greasing only every 40 hours.
- Non adjustable clutch has cooling fins for maximum clutch disc heat dissipation, leading to longer life clutch linings. The clutch also has internal stops so the clutch body cannot be damaged if linings are severely worn.
- Triple shock couplers better absorb shock loads through the drive system.

- Domed deck design improves deck strength, cutting performance and cleaning.
- Continuously welded 10 gauge deck improves strength and also reduces rusting.
- Deck protection rings help prevent blades from coming through the deck.
- Specially designed rear slope improves material distribution.
- Rectangular deck construction allows for a full 127" material distribution.
- Larger spun-formed, balanced pans with replaceable blade bolt bushing provide more blade support.
- Two piece replaceable skid shoes.
- Easy to replace safety chains.

## SPECIFICATIONS

Cutting Width	<b>127" (3.225m)</b>
Overall Width	<b>136.5" (3.467m)</b>
Overall Length Semi Mount	<b>126" (3.2m)</b>
Overall Length Trailing	<b>165" (4.191m)</b>
Cutting Height	<b>2" - 14" (50 - 355mm)</b> (depending upon tire size)
Weight Semi Mount	<b>2915 lbs (1323kg)</b> (single chain)
Weight Semi Mount Swing	<b>3145 lbs (1418kg)</b> (single chain)
Weight Trailing	<b>3185 lbs (1445kg)</b> (single chain)
Cutting Capacity	<b>2" (51mm)</b>
Minimum Tractor Size	<b>50 hp (40kw)</b>
Blade Tip Speed	<b>16100 ft/min (4908 meters/minute)</b>
Blade Overlap	<b>5" (127mm)</b>
T Box rating	<b>205 hp (153kw)</b>
Down Box rating	<b>190 hp (142kw)</b>
Deck Thickness	<b>.135" (10 ga) (3.5mm)</b>
Skirt Thickness	<b>1/4" (6.4mm)</b>
Semi Mount Hitch	<b>Cat 2 &amp; 3</b> <b>Cat 2 &amp; 3 Quick Attach</b>

## OPTIONS

Equal angle trailing, Semi mount or Semi mount swing unit;  
Single or Double Chain; Available with partial front belting; Shredder blade kit; Tires (laminated, aircraft or light truck)



- Deck protection rings and baffling for even distribution of material -

# SCHULTE



**Schulte Industries Ltd.**

P.O. Box 70, Englefeld, Saskatchewan, Canada S0K 1N0

Tel: (306) 287-3715 Fax: (306) 287-3355

E-Mail: [info@schulte.ca](mailto:info@schulte.ca)

Visit our Web site at: [www.schulte.ca](http://www.schulte.ca)

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design, specification of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.



ISO 9001

Sold By:

PRINTED IN CANADA

PREPARED by NELSON GRAPHIC DESIGN

200909