

SCHULTE®

S70 ROTARY CUTTER



Heavy Duty Cutter at a Mid-Range Price



- 1** Strong, continuous welded deck.
- 2** Deck protection ring (3/8" x 2 1/2") prevents bent blade from contacting upper deck.
- 3** High quality 160 HP gearcase is mounted to the deck with a 3/4" thick flange and 6 mounting bolts. Nuts are locked in place allowing the bolts to be retightened from the top side.
- 4** A rugged 4 plate slip clutch protects the Category 4 drive line.
- 5** Spun formed round stump jumpers ride over obstructions and prevent twine and wire from wrapping around the gearbox output shaft.
- 6** Super updraft heat treated blades provide the suction needed to cut material that has been flattened by the tractor.
- 7** Extra-long replaceable skid shoes add strength to the 10 3/8" tall side skirts.
- 8** Dual Tail Wheels are standard equipment on 3-point hitch model.
- 9** Standard double safety chains.

G O N U M B E R O N E . . . G O S C H U L T E !

Heavy Duty Cutter at a Mid-Range Price

The S70 is built tough with the size and strength you require to handle demanding jobs. On close inspection, you will discover many quality and performance features that make it the best value mower in its class. This tough cutter will cut up to 2" material. Additional blades are available to enhance shredding performance.

A super clean deck surface is easily swept clean to prevent rusting. As well, continuous welded seams add strength.

SPECIFICATIONS S70 ROTARY CUTTER

Cutting Width	84" (2.13 m)
Overall Width	91" (2.31 m)
Overall length, pull type	161" (4.09 m)
Overall length, 3-point	123" (3.12 m)
Cutting height	2" to 16" (50 mm to 406 mm)
Ground clearance	14" (356 mm)
Weight, pull type	1825 lbs. (maximum) (828 kg)
Weight, 3point	1500 lbs. (maximum) (680 kg)
Cutting capacity	2" material (50 mm)
Minimum tractor size	
3-Point Hitch Type	55HP (41 kW)
Pull Type	35HP (26 kW)
Blade tip speed	169 mph (14,850 ft/min.)
Spindle speed	675 rpm
Gearcase rating	160 HP
Side skirt depth	10.4" (264 mm)
Deck thickness	.135" (10GA) (3.5 mm)
Skirt thickness	.179" (7GA) (4.5 mm)
Three point hitch	CAT 2 or 3
	CAT 2 or 3 Quick Hitch
Drive line protection	4 plate slip clutch
Blade holder	Spun formed round pan (stump jumper)

OPTIONS

Solid laminated tires or aircraft tires.



The S70 mower is available in both pull type or three point hitch models.

Parallel-lift mechanism on pull type model keeps the unit level at cutting heights. A telescope rod linking the hitch to the rear wheel arms allows the hitch to float free should the skids encounter an obstruction.

A swivelling hitch tongue allows the unit to negotiate rough terrain. A hydraulic cylinder with hoses is included on the pull type unit.

An 80° constant velocity drive shaft allows super tight turns without any drive line chatter. The drive shaft is two pieces rather than one piece found on competitive equipment.

Category 2 and 3 standard three point hitch or Quick Hitch mounting comes with three point models.

The top link of the three point hitch system is totally free floating, allowing the cutter to traverse the most uneven terrain and still maintain an even cut.

A cutter of this size needs **dual tail wheels** so SCHULTE makes them standard, including 5" wide tires and top quality hubs with greasable, tapered roller bearings.

Schulte Industries Ltd. reserves the right to change the design, material and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment. Part No. 1000-157

Sold By:

SCHULTE



Schulte Industries Ltd.

P.O. Box 70, Englefeld, Saskatchewan, Canada S0K 1N0

Tel: (306) 287-3715 Fax: (306) 287-3355

E-Mail: info@schulte.ca

Visit our Web site at: www.schulte.ca

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design, specification of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.



PRINTED IN CANADA

PREPARED BY NELSON GRAPHIC DESIGN

201009