

SCHULTE®

XH600 ROTARY CUTTER



Designed to Work in the Toughest Terrain



- 1** A continuous welded 7 gauge deck and 1/4" side bands are standard.
- 2** A 1/2" thick x 2" deep steel protection ring on the underside of the deck eliminates any possibility of damage due to a bent blade.
- 3** A steel and rubber sandwich is used on the discharge side of the deck to protect it from damage.
- 4** A heavy duty four plate slip clutch transmits more than enough power for the toughest work.
- 5** The trailing hitch kit includes a standard constant velocity 80° universal joint to allow the tightest turns without drive line vibration.
- 6** A floating lift linkage on the trailing hitch kit allows the machine to handle rough terrain with ease.
- 7** The top link of the 3pt hitch kit is totally free floating to control the machine over the roughest terrain.

G O N U M B E R O N E . . . G O S C H U L T E !

Designed to Work in the Toughest Terrain

Built to easily handle your toughest cutting jobs! Pull type or rear mounted models for 540 rpm tractors.

Proven in the roughest conditions, these cutters have the quality and strength required to handle all your cutting work, from heavy brush cutting to mowing grass.

Gearbox and blade assemblies are the same proven designs used on Schulte's larger commercial cutters.

SPECIFICATIONS

Cutting width	72" (1.829 m)
Overall width	79" (2.007 m)
Overall length	148" (3.759 m) (Trailing hitch kit)
Overall length	112" (2.845 m) (3PT hitch kit)
Cutting height	2-15" (51-381 mm) (Trailing hitch kit)
Transport clearance	14" (356 mm) (Trailing hitch kit)
Approximate weight	1610 lbs. (730 kg) (Trailing hitch kit)
Approximate weight	1340 lbs. (608 kg) (3PT hitch kit)
Cutting capacity	4" (102 mm) (diamtere material)
Minimum tractor HP	45 (34 Kw)
Blade tip speed	15, 268ft/min (4654 m/min)
Gear box rating	160 HP
Double safety chains	Standard equipment

OPTIONS

Trailing hitch kit or 3PT hitch kit, solid laminated tires, light truck or aircraft tires on trailing unit.



STANDARD FEATURES

540 RPM drive line, round skid pans (stump jumpers), replaceable skid shoes, 7GA deck, **deck protection ring, rubber mounted discharge reinforcement plate.**

The XH600, either 3-point hitch or pull type, is designed to work in the toughest terrain while providing a superior cut.

Schulte has the right combination of hitch options, tire options and blade options to best configure your XH600 to suit your cutting requirements and budget.



Deck protection ring



Baffle plate



Floating link



Schulte Industries Ltd.

P.O. Box 70, Englefeld, Saskatchewan, Canada S0K 1N0

Tel: (306) 287-3715 Fax: (306) 287-3355

E-Mail: info@schulte.ca

Visit our Web site at: www.schulte.ca

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design, specification of it's products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.



ISO 9001

Sold By:

PRINTED IN CANADA

PREPARED by NELSON GRAPHIC DESIGN

201008