FX-320/FX-214 ROTARY CUTTER

- A single-domed 7ga continuously welded deck makes the cutter extremely easy to clean, prevents water pooling, rusting and helps shed debris
- Available in two cutting widths FX-320 20’ (6.1m) and FX-214 14’ (4.34m)
- The drive system features Cat 5 CV (1000 RPM), Cat 6 CV (540 RPM) and Cat 6 wing drivelines which employ self-adjusting friction clutches
- Equipped with Schulte Super Suction Blades with 6” blade overlap for maximum grass lift and cut
- A four gearbox driveline with independent slip clutches
- Deck protection rings are standard and protect the cutter deck from rising blades
- Large, 15” deck depth, high blade tip speeds and long gearbox shaft provide a faster cut speed
- High flex wing working range of 20° down to 90° up
- Replaceable side skirts for easier maintenance
- Optional fixed knife unit (FX-320 only) for enhanced crop residue shredding and distribution

Specifications

SPECIFICATIONS	FX-320	FX-214
Cutting Width	240” (6.1 m)	170.75” (4.34 m)
Overall Width	249” (6.32 m)	175.25” (4.45 m)
Overall Length	242” (6.15 m)	242” (6.15 m)
Cutting Height	2”- 19.5” (51 - 450 mm)	2”- 19.5” (51 - 450 mm)
Transport Width	106” (2.40 m)	108” (2.74 m)
Transport Height	120” (3.05m)	120” (3.05m)
Weight (Depends on Config.)	7500 lbs (3400 kg)	7350 lbs (3334 kg)
Hitch Weight	2280 lbs (1034 kg)	2100 lbs (953 kg)
Cutting Capacity	Fixed Knife 2” (51mm) Pan Unit 4” (102mm)	Fixed Knife 2” (51mm) Pan Unit 4” (102mm)
Minimum Tractor Size	100 HP (75 kW)	70 HP (52 kW)
Blade Tip Speed		
540 RPM	16031 ft/min (4886m/m)	16031 ft/min (4886m/m)
1000 RPM	16289 ft/min (4965m/m)	16289 ft/min (4965m/m)
Blade Overlap	6” (153mm)	6” (153mm)
Divider Gearbox Rating	260 hp (194kw)	260 hp (194kw)
Center & Wing Gearbox Rating	225 hp (168kw)*	225 hp (168kw)*
Wing Drive Shafts	Cat 6	Cat 6
Deck Thickness	.180” (7 ga) (4.6mm)	.180” (7 ga) (4.6mm)
Side Skirt Thickness	1/4” (6.4mm)	1/4” (6.4mm)
Side Skirt Depth	15” (381mm)	15” (381mm)
Wing Working Range	20° down to 90° up	20° down to 90° up
Wing Floating Range	20° down to 40° up	20° down to 40° up
Drive Size Centre and Wings	G8 / G9	G8 / G9
Drive Size Main	Cat.5CV (1000rpm) Cat.6CV (540 rpm)	Cat.5CV (1000rpm) Cat.6CV (540 rpm)
Suspension	Three rubber suspension pucks on center and single on wings	Three rubber suspension pucks on center and single on wing

FX-214- 14’ configuration with weighted side band

Available with walking axles (as shown) or straight through axles

Deck protection rings are standard



Heavy duty cast hinge line with wiper seals

Removable/replaceable side skirts

Heavy duty spun pan unit with 4” blades and pentagon blade bolts

FX-320/FX-214 FEATURES AND OPTIONS

- Optional solid laminated tires 26” or severe duty foam filled tires • Safety light kit standard
- Pro Level, Solid Tongue, Open Clevis, Equal Angle Hitch (540 RPM Only) or Precision Hitch
- 540/1000 RPM drive packages • Single chains (optional double chains) front and rear
- Front or rear half belting • Pan unit with updraft blades or shredder blade kit with optional shrouding
- Four tire kit for row crop cutting; six or eight tire kit with duels or walking axles
- Adjustable wheel standards • Optional fixed knife unit



Narrow 106”/108” transport width and over-centering wing design

Schulte Industries Ltd.
PO Box 70, Englefeld, SK Canada S0K 1N0
Ph (306) 287-3715 Fx (306) 287-3355
Email *info@schulte.ca* ***Web*** *www.schulte.ca*

MEMBER OF THE ALAMO GROUP
ALWAYS ON THE CUTTING EDGE™

Certified System
ISO 9001

Sold By:

Printed in Canada *2026/08/24*

**Intermittent use only*

Schulte is a registered trademark of Alamo Group Inc.
Schulte Industries Ltd. reserves the right to change the design and specifications of it’s products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.